

HEXFILM ULTIMA



Use less material without sacrificing safety and product protection.

Advantages of High Performance Films



Stretchability: Maximizes your equipment's stretch potential and provides excellent yield.



Load Stabilizing: Excellent memory keeps a strong grip on load.



Tear & Puncture Resistance: High tear resistance affords maximum security even around sharp package corner and edges.



Clarity: High degree of transparency for see-through packaging.



Low Noise Application: Quiet unwinding, great near telephones and offices.



Cling: Very high tack; film will cling well to product due to inside tack. Layers of film cling to the package even at high stretch levels.

Hexfilm ULTIMA: High Performance Film

When it comes to stretch wrap films for commercial and industrial use, you can count on HexFilm to have the best options for your needs. We have a broad selection of films for palletizing and bundling, from hand stretch film to machine stretch film and much more. Maximize your equipment's stretch potential with the superb cling and ultra high stretchability of our premium stretch film.

- **Uniquely formulated resin blend which achieves:**
 - ✓ Stronger stretch film
 - ✓ Higher load retention
 - ✓ High clarity
 - ✓ Low noise unwinding
- **Delivers high puncture resistance which achieves:**
 - ✓ Better load containment
 - ✓ Overall better wrapped pallet



ITEM	DESCRIPTION	TENSILE STRENGTH AT BREAK MD	TENSILE STRENGTH AT BREAK TD	ELONGATION AT BREAK MD	ELONGATION AT BREAK TD	ELMENDORF TEAR STRENGTH MD	ELMENDORF TEAR STRENGTH TD
21105	20" x 10,000' 45ga	7310 PSI ±10%	5270 PSI ±10%	668% ±10%	786% ±10%	211 g/mil ±10%	378 g/mil ±10%
20039	30" x 9000' 47ga	4500 PSI ±15%	4350 PSI ±15%	370% ±15%	575% ±15%	650 g/mil ±15%	970 g/mil ±15%
21106	20" x 6000' 50ga	7400 PSI ±10%	5690 PSI ±10%	697% ±10%	808% ±10%	290 g/mil ±10%	415 g/mil ±10%
20301	20" x 9000' 50ga	5887 PSI ±15%	4316 PSI ±15%	548% ±15%	697% ±15%	185 g/mil ±15%	265 g/mil ±15%
20009	20" x 5000' 63ga	6700 PSI ±15%	4000 PSI ±15%	480% ±15%	590% ±15%	300 g/mil ±15%	600 g/mil ±15%

Discuss with a Benchmark rep about getting a film consultation with one of our experts to learn how high performance film can optimize your film usage and reduce your cost of wrapping pallets at sales@benchmarkinc.com.